

3DM[®]-CX5-10

Inertial Measurement Unit (IMU)



3DM-CX5-10 – high-performance, industrial-grade inertial measurement unit (IMU)

The **LORD Sensing 3DM-CX5** family of high-performance, industrial-grade, board-level inertial sensors provide a wide range of triaxial inertial measurements and computed attitude and navigation solutions.

In all models, the Inertial Measurement Unit (IMU) includes direct measurement of acceleration and angular rate, and are fully temperature-compensated and calibrated over the operating temperature. The use of Micro-Electro-Mechanical System (MEMS) technology allows for highly accurate, small, lightweight devices.

The LORD Sensing **MIP Monitor** software can be used for device configuration, live data monitoring, and recording. Alternatively, the **MIP Data Communications Protocol** is available for development of custom interfaces and easy OEM integration.

PRODUCT HIGHLIGHTS

- Triaxial accelerometer, gyroscope, temperature sensors achieve the optimal combination of measurement qualities
- Smallest, lightest, highest performance IMU in its class

FEATURES AND BENEFITS

BEST IN CLASS PERFORMANCE

- Fully calibrated, temperature-compensated, and mathematically-aligned to an orthogonal coordinate system for highly accurate outputs
- High-performance, low-drift gyros with noise density of $0.005^\circ/\text{sec}/\sqrt{\text{Hz}}$ and VRE of $0.001^\circ/\text{s}/\text{g}^2\text{RMS}$
- Accelerometer noise as low as $25 \mu\text{g}/\sqrt{\text{Hz}}$

EASE OF USE


- Easy integration via comprehensive and fully backwards-compatible communication protocol
- Robust, forward compatible MIP packet protocol

COST EFFECTIVE

- Out-of-the box solution reduces development time
- Volume discounts

APPLICATIONS

- Platform stabilization, artificial horizon
- Health and usage monitoring of vehicles



3DM[®]-CX5-10 Inertial Measurement Unit (IMU)

Specifications

General		
Integrated sensors	Triaxial accelerometer, triaxial gyroscope, and temperature sensors	
Data outputs	Inertial Measurement Unit (IMU) outputs: acceleration, angular rate, delta theta, delta velocity	
Inertial Measurement Unit (IMU) Sensor Outputs		
	Accelerometer	Gyroscope
Measurement range	±8 g (standard) ±2 g, ±4 g, ±20 g, ±40 g (optional)	300°/sec (standard) ±75, ±150, ±900°/sec (optional)
Non-linearity	±0.02% fs	±0.02% fs
Bias instability	±0.04 mg	8°/hr
Initial bias error	±0.002 g	±0.04°/sec
Scale factor stability	±0.03%	±0.05%
Noise density	25 µg/√/Hz (2 g)	0.005°/sec/√/Hz (300°/sec)
Alignment error	±0.05°	±0.05°
Adjustable bandwidth	225 Hz (max)	250 Hz (max)
Offset error over temperature	0.06% (typ)	0.04% (typ)
Gain error over temperature	0.03% (typ)	0.03% (typ)
Scale factor non-linearity (@ 25°C)	0.02% (typ) 0.06% (max)	0.02% (typ) 0.06% (max)
Vibration induced noise	--	0.072°/s RMS/g RMS
Vibration rectification error (VRE)	0.03%	0.001°/s/g2 RMS
IMU filtering	Digital sigma-delta wide band anti-aliasing filter to digital averaging filter (user adjustable) scaled into physical units.	
Sampling rate	1 kHz	4 kHz
IMU data output rate	1 Hz to 1000 Hz	
Operating Parameters		
Communication	TTL serial (3.0 V dc, 9,600 bps to 921,600 bps, default 115,200)	
Power source	+ 3.2 to 5.2 V dc	
Power consumption	300 mW (typ)	
Operating temperature	-40°C to +85°C	
Mechanical shock limit	500g/1ms survivability	
Physical Specifications		
Dimensions	38 mm x 24 mm x 9.7 mm	
Weight	8 grams	
Enclosure material	Aluminum	
Regulatory compliance	ROHS, CE	
Integration		
Connectors	Data/power output: micro-DB9Samtec FTSH Series	
Software	MIP Monitor, Windows XP/Vista/7/8/10 compatible	
Compatibility	Protocol compatibility across 3DM®-GX3, GX4, RQ1, GQ4, GX5 and CV5 product families	
Software development kit (SDK)	MIP data communications protocol with sample code available (OS and platform independent)	

LORD Sensing MicroStrain
459 Hurricane Lane Suite 102
Williston, VT 05495 • USA
www.microstrain.com

Customer Support Center (in United States & Canada)
Tel: +1.802.862.6629
Email: sensing_sales@LORD.com | sensing_support@LORD.com
For a listing of our worldwide locations, visit LORD.com